



Data Sheet - APET sheet For Vacuume Forming machines

Product	APET Sheet
Type of process	Vacuume Forming machines

Sheet Parameters

Material	Material composition	structure
APET	recycled / virgin	AB,ABA

Oxygen @25°C dry	ASTM D-3985			
	250	350	450	[µm]
APET	13	9.5	7	cc/m ²

All values pertain to the original sheet and not to final product.

Slip Anti Block	Da	Silicon
colors	transparent, *opaque , *semi transparent	

*standard colors or as request by the customer

Width	245 - 1380	[mm]
Thickness	150 - 1500	[µm]

Roll weight & length tolerance	±10%	
Width tolerance	±2	[mm]
Thickness tolerance	±3%	average
	±5%	specific point

Roll property

Max. Dia.	Ø1100	[mm]	Ø6"
Min. Dia.	Ø200	[mm]	
Max. weight	900	[Kg]	
Min. weight	40	[Kg]	
core length	+0	[mm]	
	-10		
Core Dia. I.D	Ø3"	Ø6"	carton

Comments

- Roll winding - sealing Layer on inner side marked with Sticker.
- Continuity of roll : max. 2 connections in continuity of roll ,the connections are clearly marked.

Packaging

- Roll numbers, weight and length. According to attached packing list.
- Each roll wrapped in "stretch", stoppers in core ends .
- Card board sheet between layers and wooden pallet .
- Every pallet covered with PE liner .Wooden pallet lids on top of PE liner.
- Roll identification : for each roll 2 identification stickers 1 inside core 1 on roll .
- Details included : producers name ,client name , client order number , product name , product code , batch number ,width , thickness, production date, workers name, roll number.
- Pallet identification : each pallet identified by A4 size page including: product name , client name , client order number ,rolls weight and length, total number of rolls ,net and total weight, production date , inspection sticker Q.C.

